

MATERIAL SAFETY DATA SHEET



SUPER-STRIP 65 Form Releaser

HAZARD RATING: 4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = INSIGNIFICANT	HEALTH	1
	FIRE	2
	REACTIVITY	0

IDENTIFICATION

PRODUCT NAME: Super-Strip 65 Form Releaser REVISION: 1-1-09
CHEMICAL FAMILY: Hydrocarbon Mixture CAS #: Not applicable for this mixture
MANUFACTURER TELEPHONE NUMBER: (800)367-2020 IN OHIO—(419)669-2041
EMERGENCY PHONE NUMBER: (800)424-9300 CHEMTREC (Transportation Emergencies)

COMPOSITIONAL INFORMATION

For the most complete information on this MSDS section, please request our printed MSDS or e-mail Cresset@Cresset.com for a quicker electronic response.

Safety:

This product is designed to not pose hazardous conditions when used as recommended in a typical concrete site casting or plant casting operation.

OSHA, EPA and ground based DOT shipping regulations consider this product as unregulated (non-flammable) for flammability purposes.

ROUTE(S) OF EXPOSURE AND HEALTH EFFECTS

EYE CONTACT: Contact with the eye may cause mild irritation.
SKIN CONTACT: Prolonged exposure may cause mild irritation.
INHALATION: Use with adequate ventilation.
INGESTION: Although this product is not toxic it presents a pulmonary aspiration hazard if swallowed and vomiting occurs.
CARCINOGENIC: No ingredient in this product is listed as carcinogenic by IARC, NTP or OSHA.

FIRST AID PROCEDURES

EYE CONTACT: Flush with water for 15 minutes. Obtain medical assistance if irritation persists.
SKIN CONTACT: Wash with soap and water.
INHALATION: Move person to fresh air. If not breathing, give artificial respiration and obtain medical assistance.
INGESTION: Do not induce vomiting. Do not give liquids. Obtain medical assistance if large quantity is ingested.

PHYSICAL DATA

FLASH POINT: 175°F (Minimum)
DENSITY: 7.2 Pounds per Gallon
VAPOR PRESSURE: Less than Ether

SUPER-STRIP 65 Form Releaser

FIRE FIGHTING PROCEDURES AND EXTINGUISHING MEDIA

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product depending on size or potential size of fire and circumstances related to the situation. Plan fire

protection and response strategy through consultation with local fire protection authorities or appropriate specialists. Self-contained breathing apparatus and full protective clothing should be worn.

REACTIVITY

REACTION WITH WATER: Non-reactive
STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur
INCOMPATIBLE MATERIALS: Strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide or carbon monoxide upon thermal decomposition.

SPILL OR LEAK PROCEDURES

Prevent ignition, stop leak, ventilate area, contain spill by diking or impounding. Add sand, earth, or other suitable absorbent to spill area. Wear respiratory protection for large spill, leak or release. Prevent product from entering sewers, storm drains, surface waters and soil.

DISPOSAL METHODS

Dispose of contaminated product and materials used in the cleaning of spills or leaks in a manner complying with Federal, State and Local regulations.

PROTECTION INFORMATION

EYES: Safety goggles are recommended. RESPIRATORY: None under normal conditions. If fine mists are generated a NIOSH approved cartridge respirator is recommended.
SKIN: Oil impervious gloves are recommended.

DOT and EPA (Not required for MSDS)

When transported by ground in 1 gallon bottles, 5 gallon pails, 55 gallon drums, packaged and sealed by Cresset Chemical Company, this product is not regulated by the US-DOT. When transported in 275 gallon MegaPaks, must use other US-DOT regulations. See "Ground Shipping...Cresset Products" for details.

SARA Title III Regulatory Compliance Information:
Section 312 Hazard Class: Acute, chronic.
Section 313 Notification: Either none present or none present in reportable quantities.

CORPORATE STATEMENT

The information and recommendations contained herein are, to the best of Cresset Chemical Company's knowledge and belief, accurate and reliable as of the date issued. Cresset Chemical Company does not warrant or guarantee their accuracy or reliability, and shall not be

liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.



Cresset Chemical Company
One Cresset Center, Box 367
Weston, Ohio 43569

www.cresset.com
cresset@cresset.com

USA & Canada
800-367-2020
419-669-2041
FAX: 419-669-2200

FORM MS 0630 01 Jan 09
© Copyright 2009 Cresset Chemical Co.
Printed in U.S.A.