




MATERIAL SAFETY DATA SHEET



Crete-Lease "Bond Breaker"

HAZARD RATING: 4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = INSIGNIFICANT	 HEALTH	1
	 FIRE	0
	 REACTIVITY	0

IDENTIFICATION

PRODUCT NAME: Crete-Lease "Bond Breaker" REVISION: 1-1-09
CHEMICAL FAMILY: Polymer Emulsion CAS #: Not applicable for this mixture
MANUFACTURER TELEPHONE NUMBER: (800)367-2020 IN OHIO—(419)669-2041
EMERGENCY PHONE NUMBER: (800)424-9300 CHEMTREC (Transportation Emergencies)

COMPOSITIONAL INFORMATION

For the most complete information on this MSDS section, please request our printed MSDS or e-mail Cresset@Cresset.com for a quicker electronic response.

Safety:

This product is designed to not pose hazardous conditions when used as recommended in a typical concrete site casting or plant casting operation.

OSHA, EPA and ground based DOT shipping regulations consider this product as unregulated (non-flammable) for flammability purposes.

ROUTE(S) OF EXPOSURE AND HEALTH EFFECTS

EFFECTS OF OVEREXPOSURE:

HEALTH HAZARDS: None known to occur.

CARCINOGENICITY: None known to exist.

SIGNS and SYMPTOMS OF EXPOSURE: None known to occur.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known to occur.

SPECIAL PRECAUTIONS

FIRST AID: Flush skin or eyes with water. If overexposure from inhalation is thought to occur, remove to fresh air. If ingested, call a physician.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep from freezing. Keep container closed when not in use.

OTHER PRECAUTIONS:

Common sense and good manufacturing practice should be used at all times.

This MSDS complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200.

PHYSICAL DATA

FLASH POINT: None VAPOR DENSITY: Lighter Than Air
LIQUID DENSITY: Lighter Than Water BOILING RANGE: 214°F
EVAPORATION RATE: Slower than n-Butyl Acetate VOC 2 g/L
WEIGHT PER GALLON: 8.2 Pounds
APPEARANCE: White Liquid

