

# MATERIAL SAFETY DATA SHEET



## CRETE-LEASE "Latex" Mold Release - Aerosol

|  |            |          |
|--|------------|----------|
| HAZARD RATING:<br>4 = EXTREME<br>3 = HIGH<br>2 = MODERATE<br>1 = SLIGHT<br>0 = INSIGNIFICANT | HEALTH     | <b>2</b> |
|  | FIRE       | <b>4</b> |
|  | REACTIVITY | <b>0</b> |
|  |            |          |

### IDENTIFICATION

PRODUCT NAME: CRETE-LEASE "Latex" Mold Release - Aerosol REVISION: 1-1-09  
CHEMICAL FAMILY: Fatty acid ester/alcohol blend CAS #: Not applicable for this mixture  
MANUFACTURER TELEPHONE NUMBER: (800)367-2020 IN OHIO—(419)669-2041  
EMERGENCY PHONE NUMBER: (800)424-9300 CHEMTREC (Transportation Emergencies)

### COMPOSITIONAL INFORMATION

For the most complete information on this MSDS section, please request our printed MSDS or e-mail [Cresset@Cresset.com](mailto:Cresset@Cresset.com) for a quicker electronic response.

#### Safety:

This product is designed to not pose hazardous conditions when used as recommended in a typical concrete site casting or plant casting operation.

OSHA, EPA and ground based DOT shipping regulations consider this product as unregulated (non-flammable) for flammability purposes.

### ROUTE(S) OF EXPOSURE AND HEALTH EFFECTS

EYE CONTACT: Liquid and vapors cause eye irritation.  
SKIN CONTACT: Prolonged or repeated exposure may cause irritation.  
INHALATION: High vapor concentrations may cause respiratory tract irritation and narcosis.  
INGESTION: This product is expected to be toxic by ingestion.

### FIRST AID PROCEDURES

EYE CONTACT: Flush with water for 15 minutes. Obtain medical assistance if irritation persists.  
SKIN CONTACT: Wash with soap and water until no odor remains.  
INHALATION: Move person to fresh air. If breathing is difficult, administer oxygen, obtain medical assistance.  
INGESTION: Get medical attention immediately.

### PHYSICAL DATA

FLASH POINT: NA  
DENSITY: 7 Pounds per Gallon  
VAPOR PRESSURE: Aerosol

---

# Crete-Lease "Latex" Mold Release - Aerosol

---

## FIRE FIGHTING PROCEDURES AND EXTINGUISHING MEDIA

---

Alcohol foam, water spray (fog), dry chemical and carbon dioxide type extinguishing agents may all be suitable for extinguishing fires involving this type of product depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire

protection authorities or appropriate specialist. Self-contained breathing apparatus and full protective clothing should be worn.

Flammable liquid and vapor. Vapors are heavier than air and may travel along the ground or may be moved by ventilation to an ignition source and may flash back.

---

## REACTIVITY

---

|                                   |   |            |        |
|-----------------------------------|---|------------|--------|
| REACTION WITH WATER:              | Non-reactive  | STABILITY: | Stable |
| HAZARDOUS POLYMERIZATION:         | Will not occur  |            |        |
| INCOMPATIBLE MATERIALS:           | Strong oxidizing agents.                                      |            |        |
| HAZARDOUS DECOMPOSITION PRODUCTS: | Carbon dioxide or carbon monoxide upon thermal decomposition. |            |        |

---

## SPILL OR LEAK PROCEDURES

---

Prevent ignition, stop leak, ventilate area, contain spill by diking or impounding. Add sand, earth, or other suitable absorbent to spill area. Wear respiratory protection for large spill, leak or release. Prevent product from entering sewers, storm drains, surface waters and soil.

---

## DISPOSAL METHODS

---

Dispose of contaminated product and materials used in the cleaning of spills or leaks in a manner complying with Federal, State and Local regulations.

---

## PROTECTION INFORMATION

---

|       |  |              |  |
|-------|--|--------------|--|
| EYES: | Use splash proof chemical goggles or face shield when eye contact may occur. | RESPIRATORY: | Use with adequate ventilation. Ventilate as needed to comply with exposure limit. In the event of vapor concentrations exceeding the time weighted exposure limit use a NIOSH approved cartridge respirator or gas mask. |
| SKIN: | Impervious gloves are recommended.   |              |  |

---

## DOT and EPA (Not required for MSDS)

---

When transported by ground, by common carrier or by UPS, this product requires ORM-D Label.

---

## CORPORATE STATEMENT

---

The information and recommendations contained herein are, to the best of Cresset Chemical Company's knowledge and belief, accurate and reliable as of the date issued. Cresset Chemical Company does not warrant or guarantee their accuracy or reliability, and shall not be

liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.

---



**Cresset Chemical Company**  
One Cresset Center, Box 367  
Weston, Ohio 43569

**www.cresset.com**  
cresset@cresset.com

**USA & Canada**  
**800-367-2020**  
419-669-2041  
FAX: 419-669-2200

FORM MS 0724 01 Jan 09  
© Copyright 2009 Cresset Chemical Co.  
Printed in U.S.A.