

# MATERIAL SAFETY DATA SHEET



## SPATTER-COTE 100-Xtra Spatter Protection

HAZARD RATING: 4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = INSIGNIFICANT	HEALTH	<b>1</b>
	FIRE	<b>1</b>
	REACTIVITY	<b>0</b>

### IDENTIFICATION

PRODUCT NAME: Spatter-Cote 100-Xtra Spatter Protection REVISION: 1-1-09  
CHEMICAL FAMILY: Hydrocarbon Mixture CAS#: Not applicable to mixture.  
MANUFACTURER TELEPHONE NUMBER: (800) 367-2020 In Ohio—(419) 669-2041  
EMERGENCY PHONE NUMBER: (800) 424-9300 CHEMTREC (Transportation Emergencies)

### COMPOSITIONAL INFORMATION

For the most complete information on the MSDS section, please request our printed MSDS or e-mail [Cresset@Cresset.com](mailto:Cresset@Cresset.com) for a quicker electronic response.

#### Safety:

This product is designed to not pose hazardous conditions when used as recommended in a typical concrete site casting or plant casting operation.

OSHA, EPA and ground based DOT shipping regulations consider this product as unregulated (non-flammable and non-toxic) for toxicity and flammability purposes.

### ROUTE(S) OF EXPOSURE AND HEALTH EFFECTS

EYE CONTACT: May cause irritation or in extreme cases may burn eyes.  
SKIN CONTACT: Prolonged or repeated contact may cause irritation.  
INHALATION: Inhalation of vapors may cause nausea or irritation to the respiratory tract. Excessive exposures may cause dizziness or other central nervous system effects.  
INGESTION: This product has a low order of acute toxicity. Pulmonary aspiration hazard if swallowed and vomiting occurs.  
CARCINOGENIC: No ingredient in this product is listed as carcinogenic by IARC, NTP or OSHA.

### FIRST AID PROCEDURES

EYE CONTACT: Wash eyes immediately with water for 15 min. If irritation persists, get immediate medical attention.  
SKIN CONTACT: Flush area with water, then soap and water.  
INHALATION: Move away from vapors to fresh air source. Rest until normal breathing is restored. If not breathing, give artificial respiration and obtain medical assistance.  
INGESTION: Do not induce vomiting. Get immediate medical attention.

### PHYSICAL DATA

FLASH POINT: 210°F (Combustible)  
DENSITY: 7.0 Pounds per Gallon  
VAPOR PRESSURE: Less than Ether

---

# SPATTER-COTE 100-Xtra MATERIAL SAFETY DATA SHEET

---

## FIRE FIGHTING PROCEDURES AND EXTINGUISHING MEDIA

---

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product depending on size or potential size of fire and circumstances related to the situation. Plan fire

protection and response strategy through consultation with local fire protection authorities or appropriate specialist. Self-contained breathing apparatus and full protective clothing should be worn.

---

## REACTIVITY

---

REACTION WITH WATER: Non-reactive  
STABILITY: Stable  
HAZARDOUS POLYMERIZATION: Will not occur  
INCOMPATIBLE MATERIALS: Strong oxidizing agents  
HAZARDOUS DECOMPOSITION: Carbon dioxide and carbon monoxide.

---

## SPILL OR LEAK PROCEDURES

---

Prevent ignition, stop leak, ventilate area, contain spill by diking or impounding. Add sand, earth, or other suitable absorbent to spill area. Wear respiratory protection for large spill, leak or release. Prevent product from entering sewers, storm drains, surface waters and soil.

---

## DISPOSAL METHODS

---

Dispose of contaminated product and materials used in the cleaning of spills or leaks in a manner complying with Federal, State and Local regulations.

---

## PROTECTION INFORMATION

---

EYES: Use splash proof chemical goggles or face shield when eye contact may occur.  
SKIN: Use impervious gloves if prolonged or repeated skin contact cannot be avoided. Wash skin thoroughly after contact.  
RESPIRATORY: Use with adequate ventilation. Ventilate as needed to comply with exposure limit. In the event of vapor concentrations exceeding the time weighted exposure limit use a NIOSH approved cartridge respirator or gas mask.

---

## DOT and EPA (Not required for MSDS)

---

When transported by ground in 1 gallon bottles, 5 gallon pails, 55 gallon drums or 275 gallon MegaPaks, packaged and sealed by Cresset Chemical Company, this product is not regulated by the US-DOT.

**SARA Title III Regulatory Compliance Information:**  
Section 312 Hazard Class: Acute, chronic.  
Section 313 Notification: Either none present or none present in reportable quantities.

---

## CORPORATE STATEMENT

---

The information and recommendations contained herein are, to the best of Cresset Chemical Company's knowledge and belief, accurate and reliable as of the date issued. Cresset Chemical Company does not warrant or guarantee their accuracy or reliability, and shall not be

liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.

---



**Cresset Chemical Company**  
One Cresset Center, Box 367  
Weston, Ohio 43569

**www.Cresset.com**  
cresset@cresset.com

**USA and Canada**  
**800-367-2020**  
419-669-2041  
FAX: 419-669-2200

FORM MS 0 01 Jan 09  
© Copyright 2009 Cresset Chemical Co.  
Printed in U.S.A.