




MATERIAL SAFETY DATA SHEET



Crete-Lease "Bond Breaker-Xtra"

HAZARD RATING: 4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = INSIGNIFICANT	 HEALTH	1
	 FIRE	0
	 REACTIVITY	0

IDENTIFICATION

PRODUCT NAME: Crete-Lease "Bond Breaker-Xtra" REVISION: 1-1-09
CHEMICAL FAMILY: Polymer Emulsion CAS #: Not applicable for this mixture
MANUFACTURER TELEPHONE NUMBER: (800)367-2020 IN OHIO—(419)669-2041
EMERGENCY PHONE NUMBER: (800)424-9300 CHEMTREC (Transportation Emergencies)

COMPOSITIONAL INFORMATION

For the most complete information on the MSDS section, please request our printed MSDS or e-mail Cresset@Cresset.com for a quicker electronic response.

Safety:

This product is designed to not pose hazardous conditions when used as recommended in a typical concrete site casting or plant casting operation.

OSHA, EPA and ground based DOT shipping regulations consider this product as unregulated (non-flammable and non-toxic) for toxicity and flammability purposes.

ROUTE(S) OF EXPOSURE AND HEALTH EFFECTS

EFFECTS OF OVEREXPOSURE:

HEALTH HAZARDS: None known to occur.

CARCINOGENICITY: None known to exist.

SIGNS and SYMPTOMS OF EXPOSURE: None known to occur.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known to occur.

SPECIAL PRECAUTIONS

FIRST AID: Flush skin or eyes with water. If overexposure from inhalation is thought to occur, remove to fresh air. If ingested, call a physician.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep from freezing. Keep container closed when not in use.

OTHER PRECAUTIONS:

Common sense and good manufacturing practice should be used at all times.

This MSDS complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200.

PHYSICAL DATA

FLASH POINT: None VAPOR DENSITY: Lighter Than Air
LIQUID DENSITY: Lighter Than Water BOILING RANGE: 214°F
EVAPORATION RATE: Slower than n-Butyl Acetate VOC 2 g/L
WEIGHT PER GALLON: 8.2 Pounds
APPEARANCE: White Liquid

Crete-Lease "Bond Breaker-Xtra"

FIRE FIGHTING PROCEDURES AND EXTINGUISHING MEDIA

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product depending on size or potential size of fire and circumstances related to the situation. Plan fire

protection and response strategy through consultation with local fire protection authorities or appropriate specialists. Self-contained breathing apparatus and protective clothing should be worn.

REACTIVITY

REACTION WITH WATER: Non-reactive STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur
INCOMPATIBLE MATERIALS: NA
HAZARDOUS DECOMPOSITION PRODUCTS: None known to exist.

SPILL OR LEAK PROCEDURES

Flush small quantities with excess water. Larger amounts should be absorbed onto appropriate material, (e.g., sawdust).

DISPOSAL METHODS

Dispose of contaminated product and materials used in the cleaning of spills or leaks in a manner complying with Federal, State and Local regulations.

PROTECTION INFORMATION

EYES: Safety glasses are recommended. RESPIRATORY: None usually required.
SKIN: Use impervious gloves if repeated or VENTILATION: General mechanical ventilation
prolonged contact is expected. is recommended.

DOT and EPA (Not required for MSDS)

When transported by ground or air in 1 gallon bottles, 5 gallon pails, 55 gallon drums or 275 gallon MegaPaks, packaged and sealed by Cresset Chemical Company, this product is not regulated by the US-DOT.

SARA Title III Regulatory Compliance Information:
Section 312 Hazard Class: Not required.
Section 313 Notification: Either none present or none present in reportable quantities.

CORPORATE STATEMENT

The information and recommendations contained herein are, to the best of Cresset Chemical Company's knowledge and belief, accurate and reliable as of the date issued. Cresset Chemical Company does not warrant or guarantee their accuracy or reliability, and shall not be

liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.



Cresset Chemical Company
One Cresset Center, Box 367
Weston, Ohio 43569

www.cresset.com
cresset@cresset.com

USA & Canada
800-367-2020
419-669-2041
FAX: 419-669-2200

FORM MS 0 01 Jan 09
© Copyright 2009 Cresset Chemical Co.
Printed in U.S.A.