



Environmental Report Card

- ✓ Non-flammable
- ✓ VOC compliant
- ✓ Non-carcinogenic
- ✓ Solventless
- ✓ Water based

FORM CLEANER 240

Rust Remover

Specification Sheet

1. PRODUCT NAME

Form Cleaner 240 Rust Remover

2. MANUFACTURER

Cresset Chemical Co., Inc.
 One Cresset Center
 Weston, OH 43569
800-367-2020 USA & Canada
 419-669-2041
 (FAX) 419-669-2200
 www.cresset.com
 cresset@cresset.com

3. PRODUCT DESCRIPTION

Basic Use: Use Form Cleaner 240 Rust Remover to remove rust from steel forms, iron railings, etc. It also eats away concrete build-up. It:

- Is a thick, pasty gel or “jelly”
- Protects treated forms from rust
- Promotes bonding of paints
- Quickly dissolves rust
- Meets Federal VOC standards

Limitations: Do not use on chrome.

Caution: Contains Phosphoric acid. Corrosive. Avoid contact with skin and eyes. Wear rubber gloves when using. Use in a well ventilated area. For eye contact, flush with water for 15 minutes, call a physician. For skin contact, wash thoroughly with soap and water. If swallowed, do not induce vomiting, give large quantities of water to drink, call a physician. **KEEP OUT OF REACH OF CHILDREN.**

Ground Shipping in the USA: Containers holding more than 1 liter (more than a quart) require federally mandated procedures for the driver, container and shipping papers. See Cresset brochure “Ground Shipping” for details.

TABLE OF PROPERTIES

Freeze Thaw Stability	Do Not Freeze
Flash Point	N/A
Pounds Per Gallon	9.5
pH	1

Composition: A proprietary blend of Phosphoric acid. Contains no silicones or carcinogens.

4. TECHNICAL DATA

Please see Table.

5. APPLICATION

Preparatory Work: Use gloves. Scrape off loose rust from form.

Application: Brush or roll on and work into pitted areas. Leave on for about 10 minutes. Rinse with fresh water.

Repeat if any rust or concrete build-up remain on form. For heavily rusted items, can leave it on for longer times since it has little effect on unruined steel.

Though it provides its own rust protection, it is somewhat temporary. Paint it within a day or coat forms with Cresset’s Store-Cote RP-6 Rust Preventative (which is compatible with concrete form release procedures) for longer lasting protection.

Leaving it on for too long may cause it to harden. To remove, just work in a little more Form Cleaner 240.

Wipe it off painted surfaces immediately, as it removes some paint.

6. AVAILABILITY AND COST

Availability: Form Cleaner 240 Rust Remover is available in 1 and 5 gallon containers; recyclable, orange and white plastic 55 gallon drums and 275 gallon MegaPaks. Contact Cresset Chemical Company for your nearest distributor.

Cost: The cost on hard, smooth surfaces is about \$0.06 per square foot (January 2007).

7. LIMITED WARRANTY

Cresset Chemical Company warrants the product against defects in materials for a period of 1 year from purchase. If Cresset receives notice of such defects during the warranty period, Cresset at its option will either replace the product or refund the purchase price. THE WARRANTY SET FORTH ABOVE IS EXCLUSIVE AND NO OTHER WARRANTY, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED. CRESSET SPECIFICALLY DISCLAIMS THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE REMEDIES PROVIDED HEREIN ARE BUYER’S SOLE AND EXCLUSIVE REMEDIES. IN NO EVENT SHALL CRESSET CHEMICAL COMPANY BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOSS OF PROFIT) WHETHER BASED ON CONTRACT, TORT OR ANY OTHER LEGAL THEORY.

8. MAINTENANCE

Not required.

9. TECHNICAL SERVICES

To keep you abreast of new ideas in the development, selection and application techniques of release agents, we publish newsletters, technical brochures, specification sheets and Material Safety Data Sheets.