



Environmental Report Card

- ✓ Non-toxic
- ✓ Non-flammable
- ✓ VOC compliant
- ✓ Solventless

STORE-COTE® RP6-Xtra Rust Preventative with Poly-Release® Specification Sheet

1. PRODUCT NAME

Store-Cote RP6-Xtra Rust Preventative w/Poly-Release®

2. MANUFACTURER

Cresset Chemical Co., Inc.
One Cresset Center
Weston, Ohio 43569
800-367-2020 USA & Canada
419-669-2041
(FAX) 419-669-2200
www.cresset.com
cresset@cresset.com

3. PRODUCT DESCRIPTION

Basic Use: Store-Cote RP6-Xtra Rust Preventative w/Poly-Release is applied to steel equipment and forms to protect them from rusting. It:

- Applies with same equipment used for release agents
- Is a heavy liquid and stays “wet” — does not harden or dry
- Can stay on form, complete removal for form reuse, not necessary
- Reduces skin rashes to a minimum
- Has a very low odor
- Has no flammable solvents
- Provides protection for about 6 months
- Is not harmful to painted surfaces
- Can also work as a release agent
- Will also help preserve plywood forms

Limitations: Overspray on SBR or natural rubber should be removed within hours. Commonly available degreasers will remove overspray.

Light rusting may occur on sand-blasted steel.

TABLE OF PROPERTIES

	Containers	
	Aerosol	All Others
Color	Straw	Straw
Opacity	Clear	Clear
Freeze Temperature	N/A	-10°F (-23°C)
Freeze Damage	None	None
Flash Point	N/A	250°F (120°C)
Viscosity (centipoises)	40	40 @ 68°F (20°C)
Pounds per gallon	7.45	7.45
VOC	Exempt	145 g/L

Composition: A proprietary blend of neutralized vegetable oils in a heavy mineral oil. Contains no waxes, no silicones...no carcinogens.

Ground Shipping in the USA: Containers holding 275 gallons or 55 gallons or 5 gallons or less (regardless of quantity) are not federally regulated and shipping product in the Cresset package does not require following hazardous shipping requirements.

4. TECHNICAL DATA

Please see Tables.

5. APPLICATION

Basic Use: Which type of rust preventative is best for your application...drying type coating (paint), wax types or liquids? Though the drying and wax types can virtually eliminate rust for years they are expensive to remove before reuse of the equipment.

Liquid Store-Cote RP6-Xtra w/Poly-Release is sprayable with your existing spray equipment and it

does not have to be removed before reusing the forms.

Liquid Store-Cote RP6-Xtra w/Poly-Release gives excellent protection for several months, especially when applied to dry, clean steel.

Preparatory Work: Remove any build-up from steel forms or equipment. Store-Cote RP6-Xtra w/Poly-Release is typically applied with a sprayer—though brush, mop or even dipping is effective.

Methods: Apply to dry, clean steel forms or equipment by any convenient method. Just be sure the

COVERAGE WITH STORE-COTE RP6-Xtra w/Poly-Release®

Form Surface	(sq ft/gal)
Hard & Smooth	800

TYPICAL FORM STORAGE TIMES	Ocean Air Environment	Up to 2 Months
	Outdoors in Moderate Climate	Up to 6 Months
	Indoors	Up to 9 Months

equipment is completely wetted by Store-Cote RP6-Xtra w/Poly-Release. Overapplication promotes better protection.

If spots of rust should occur during storage, just re-apply Store-Cote RP6-Xtra w/Poly-Release over affected area.

Sprayer Comments: Use same sprayer as used to apply release agents. No special steps, other than cleaning out the sprayer before and after use, need to be considered before using Store-Cote RP6-Xtra w/Poly-Release.

Putting Forms Back into Use: When forms are needed again, just wipe off any accumulated dust or debris and spray with a Crete-Lease Release Agent.

Forms need only to be wiped off—cleaning solvents and degreasers are not required. Scraping is not needed.

Storage: Factory sealed containers will keep up to 2 years at temperatures from -20°F to 140°F (-30°C to 60°C). As a class 3B liquid, Section 1910.106 of OSHA Standards does not apply for storage purposes.

Precautions: Keep out of reach of children. Avoid prolonged contact with the skin. Use with adequate ventilation. See Material Safety Data Sheet for additional information.

6. AVAILABILITY AND COST

Availability: Store-Cote RP6-Xtra w/Poly-Release is available in 1 and 5 gallon containers; orange and white striped 55 gallon drums and 275 gallon MegaPaks. Contact Cresset Chemical Company for your nearest distributor.

Cost: The cost on hard, smooth surfaces is about \$0.01 per square foot (January 2007).

7. LIMITED WARRANTY

Cresset Chemical Company warrants the product against defects in materials for a period of 1 year from purchase. If Cresset receives notice of such defects during the warranty period, Cresset at its option will either replace the product or refund the purchase price. THE WARRANTY SET FORTH ABOVE IS EXCLUSIVE AND NO OTHER WARRANTY, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED. CRESSET SPECIFICALLY DISCLAIMS THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE REMEDIES PROVIDED HEREIN ARE BUYER'S SOLE AND EXCLUSIVE REMEDIES. IN NO EVENT SHALL CRESSET CHEMICAL COMPANY BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOSS OF PROFIT) WHETHER BASED ON CONTRACT, TORT OR ANY OTHER LEGAL THEORY.

8. MAINTENANCE

Not required.

9. TECHNICAL SERVICES

Cresset Chemical Company specializes in developing, distributing and servicing release agents. Our technical support includes assistance in optimizing concrete mixtures for achieving architectural surfaces; release agent compatibility with superplasticizers, coatings, form facings, etc.; and solving other concrete surface blemish problems.

Free literature includes:

- Catalog of Products
- "Cresset Concrete Standards" (Application techniques to obtain high visual impact concrete surfaces)
- "Surface Voids and How to Eliminate Them"

Over 75 distributors in the United States, Canada, Australia and Germany to serve you. Your technical inquiries are welcome, please call, write or FAX.